



1999

NETWORK WALKIE TALKIE

- Global communication
- Low power alarm
- Group call/ private call/ Nested-group call
- Program/Upgrade OTA mode
- Tx volume adjustable
- GPS optional
- Dual SIM
- Noise cancellation optional
- VOX optional

Technical

Network Walkie Talkie **1999**

Working voltage: 3.7V
Battery: 3200mAh
Operation system: RTOS
Solution: ASR1606
Language: English
Display: 1.4inch
Max Tx output power: 23dBm±2dBm@Aupbts
Rx sensitivity: -106dBm
Antenna: Built-in antenna
Working temperature: -20~60°C
Storage temperature: -20~60°C
Audio output power: 2W@10% distortion
Size: 127.2x60.6x35.5mm (with antenna)
Weight: 148.9g (battery included)
Earphone: K-type
Charger: Type-C cable

3GPP Band	Send	Receive	Unit
LTE-FDD B1	1920-1980	2110-2170	MHz
LTE-FDD B3	1710-1785	1805-1880	MHz
LTE-FDD B8	880-915	925-960	MHz
LTE-FDD B34	2010-2025	2010-2025	MHz
LTE-TDD B38	2570-2620	2570-2620	MHz
LTE-TDD B40	2300-2400	2300-2400	MHz
LTE-TDD B41	2495-2690	2495-2690	MHz

Accessory



Battery



Type-C cable



Belt clip

